

RT-W15U-6080



Technical Preview

- Main material: Cold-rolled steel SPP.
- Thickness: mounting profile 2.0mm, mounting angle 1.5mm, others 1.2mm.
- Exquisite design with precise dimensions and craftsmanship.
- Dimensions Width 600 , Height 700 and Depth 800 mm.
- Tempered Glass Door 5.00mm. / Vented Door (option).
- Optional locks for side panels.
- Closable top/bottom cable entry openings;
- Removable side panels and front/back doors for operation and watching;
- 1 FAN installed and Extra Fan can be installed Option.
- Moon Lock shape.
- Doors can be opened from the left or right.
- Surface treatment: Degreasing, pickling, phosphate, laundering, powder coating
- Protection class: IP20
- Load capacity Static load: 100KG
- PDU 6 WAYS with the Package.
- 1 Shelf with the Package.
- Castors Can be installed (Option).

RT-W15U-6080 Technical Parameters:

NAMES	QTY	SURFACE TREATMENT	UNIT	MATERIALS
TOP COVERS	1	Powder coating	PC	1.2 mm cold-rolled steel
BOTTOM PLATES	1	Powder coating	PC	1.2 mm cold-rolled steel
FRAMES	2	Powder coating	PC	1.2 mm cold-rolled steel
FRONT DOOR	1	Powder coating	PC	5.0 mm Tempered Glass
SIDE DOOR	2	Powder coating	PC	1.0 mm cold rolled steel
SIDE PANELS	2	Powder coating	PC	1.2 mm cold-rolled steel
HORIZONTAL BRACKETS	4	Powder coating	PC	1.2 mm cold-rolled steel
L-SHAPED PANELS	2	Powder coating	PC	1.2 mm cold-rolled steel
BACK PANELS	1	Powder coating	PC	1.2 mm cold-rolled steel
WALL HANGING PANELS	1	Powder coating	PC	1.2 mm cold-rolled steel
PROFILE RAILS	4	Powder coating	PC	1.5 mm cold-rolled steel
CAGE NUTS	20	Powder coating	PC	

Dimensions and Packing

TYPES	RTW-15U6080
CAPACITY(U)	15U
WIDTH	600
/DEPTH	800
/HEIGHT	670
WHOLE PACKGE	
WIDTH	620
/DEPTH	820
/HEIGHT	790
VOLUME	0.31
FLAT PACKAGE	
PACKING	170*790*208
VOLUMES M3	0.89