

RT-W6U-6045



- Exquisite design with precise dimensions and craftsmanship.
- Easy installation.
- Main material: Cold-rolled steel ,
- Thickness: mounting profile 2.0mm, mounting angle 1.5mm, others 1.2mm.
- Dimensions : Width 600 Depth 450 , Height 300 mm.
- Tempered Glass Door 5.0mm.
- With locks for side panels;
- Side can be opened from the left or right;
- Closable top/bottom cable entry openings;
- Removable side panels and front/back doors for operation and watching;
- 1 Fan 12' installed with Metal Grid.
- Surface treatment: Degreasing, pickling, phosphate, laundering, powder coating;
- Protection class:IP20
- Load capacity: Static load:60KG
- PDU 6 WAYS with the package.
- 1 Shelf with the package.
- Comply with ANS/EIA RS-310-D, IEC297-2, DIN41491, PART1: Part 1 & 7, ETSI Standards

RT-W6U-6045 Technical Parameters:

NAMES	QTY	SURFACE TREATMENT	UNIT	MATERIALS
top covers	1	Powder coating	PC	1.2 mm cold-rolled steel
bottom plates	1	Powder coating	PC	1.2 mm cold-rolled steel
frames	2	Powder coating	PC	1.2 mm cold-rolled steel
FRONT DOOR	1	Powder coating	PC	5.0 mm Tempered Glass
SIDE DOOR		Powder coating	PC	1.0 mm cold rolled steel
side panels	2	Powder coating	PC	1.2 mm cold-rolled steel
horizontal brackets	4	Powder coating	PC	1.2 mm cold-rolled steel
L-shaped panels	2	Powder coating	PC	1.2 mm cold-rolled steel
back panels	1	Powder coating	PC	1.2 mm cold-rolled steel
wall hanging panels	1	Powder coating	PC	1.2 mm cold-rolled steel
profile rails	4	Powder coating	PC	1.5 mm cold-rolled steel
cage nuts	20	Powder coating	PC	

Dimensions and Packing

TYPES	RTW6406
CAPACITY(U)	6U
WIDTH	600
/DEPTH	450
/HEIGHT	370
WHOLE PACKGE	
WIDTH	620
/DEPTH	470
/HEIGHT	390
VOLUME	0.114
FLAT PACKAGE	
PACKING	250*470*620
VOLUMES M3	0.073