

RT-O22U-6060 Technical specs:



- RT 22U lockable floor standing Outdoor server racks are designed to protect sensitive network equipment from harsh environments where equipment may be exposed to dust or water. Made from powder-coated & welded cold rolled steel, they come in a variety of sizes with IP55 rating for extra protection from the elements.

- Dimensions: 110 Height 600 depth 600 width.

- Made from cold rolled steel

- Equipped with a Thermostat.

- Light Gray RAL 7035

- Compatible with EN60529/10.91, DIN41491, DIN41494, EIA/ECA-310-E, IEC , 294-2, RoHS.

RT-O22U-6060 Technical specs:

Features

- Supplied fully assembled
- Lockable front door
- Rain hood included
- Sealed bottom cable entry gland
- Water and dust proof polyurethane door joint strip
- Adjustable 19" mounting rails front and rear
- Grounding pin

Fully welded design, supplied complete, no assembly required

- Surface finish: Degreasing, pickling, phosphoric wash, cleaning, and powder coated

Extra Optional features:

- Front door rubber seal
- Plinth is an Option



RT-O22U-6060 Technical specs:

names	quantity	unit	materials	surface treatment	Remarks
top covers	1	pc	1.5 mm cold-rolled steel	powder coating	---
bottom plates	1	pc	1.5 mm cold-rolled steel	powder coating	---
fan plate with 4 fans	1	pc	1.5 mm cold-rolled steel	powder coating	4 fans for 600*600 racks
frames	2	pc	1.5 mm cold-rolled steel	powder coating	---
front doors	1	pc	1.5mm cold-rolled steel	powder coating	
Solid back	1	pc	1.5 mm cold-rolled steel	powder coating	
side rain hood	2	pc	1.5 mm cold-rolled steel	powder coating	---
rails	4	pc	2.0 mm cold-rolled steel	powder coating	1.5mm thick steel for less than 22U
shelves	1	pc	1.5mm cold-rolled steel	powder coating	1 pc for 18-22U, 2 pcs for 27-37U, 3 pcs (600 deep) for 42-47U
casters	4	pc	Optional	Optional	---
M12 support feet	4	pc	---	---	---
cage nuts	40	pc	---	---	20 sets for 18U-22U, 30 sets for 27-37U, 40 sets for 42-47U
sockets with 9 outlets	1	pc	---	---	---