



RackTech Cabinets

RT-W 9U-6060VS



Technical Preview

- Exquisite design with precise dimensions and craftsmanship.
- Main material: Cold-rolled steel SPP.
- Thickness: mounting profile 2.0mm, mounting angle 1.5mm, others 1.2mm.
- Dimensions : Width 600 , Depth 600 , Height 410 mm.
- Vented front Door 1.2 mm., Solid Rear.
- Optional locks for side panels.
- Closable top/bottom cable entry openings;
- Removable side panels and front/back doors for operation and watching;
- Side Panel with Lock.
- 1X Fan 12' Installed with Metal Grid.
- Vented Front Panels moon light Locks.
- Doors can be opened from the left or right;
- Surface treatment: Degreasing, pickling, phosphate, laundering, powder coating
- Protection class: IP20
- Load capacity Static load: 100KG
- PDU 6 WAYS with the Package.
- 1 Shelf with the Package.



RT-W 9U-6060VS Technical Parameters:

NAMES	QTY	SURFACE TREATMENT	UNIT	MATERIALS
TOP COVERS	1	Powder coating	PC	1.2 mm cold-rolled steel
BOTTOM PLATES	1	Powder coating	PC	1.2 mm cold-rolled steel
FRAMES	2	Powder coating	PC	1.2 mm cold-rolled steel
FRONT DOOR	1	Powder coating	PC	1.2 mm cold-rolled steel
SIDE DOOR	2	Powder coating	PC	1.0 mm cold rolled steel
SIDE PANELS	2	Powder coating	PC	1.2 mm cold-rolled steel
HORIZONTAL BRACKETS	4	Powder coating	PC	1.2 mm cold-rolled steel
L-SHAPED PANELS	2	Powder coating	PC	1.2 mm cold-rolled steel
BACK PANELS	1	Powder coating	PC	1.2 mm cold-rolled steel
WALL HANGING PANELS	1	Powder coating	PC	1.2 mm cold-rolled steel
PROFILE RAILS	4	Powder coating	PC	1.5 mm cold-rolled steel
CAGE NUTS	20	Powder coating	PC	

Dimensions and Packing

TYPES	RTW-9U6060
CAPACITY(U)	9U
WIDTH	600
/DEPTH	600
/HEIGHT	400
WHOLE PACKGE	
WIDTH	620
/DEPTH	620
/HEIGHT	420
VOLUME	0.31
FLAT PACKAGE	
PACKING	620*620*420
VOLUMES M3	0.63

